

Features

- Pure sine wave output ,input & output fully isolation
- AC charger with 4-stage charge mode, up to 25A
- High efficiency design up to 88% ,energy saving mode
- Excellent loads with 3*rated start power
- 7 LED display show the work and charging station
- Built-in LCD display, show data of working
- Built-in AC bypass relay, UPS function
- Advanced microprocessor control
- Input polarity/UVP/OVP/OSP/OLP/OTP
- Remote control RJ11



Specifications

Models	LPT800-112	LPT800-124	LPT800-212	LPT800-224
Output Power	800W			
Surge Power	2400W			
DC Input Voltage	12VDC	24VDC	12VDC	24VDC
Output Voltage	100/110/120VAC±5%		220/230/240VAC±3%	
Output Frequency	50/60Hz ±0.5%			
Output Waveform	True sine wave (THD<5%)			
Power Factor	0.1~1			
Efficiency	85%	86%	86%	87%
No Load Power	<10W (Power saving mode)			
Transfer Time	<8 ms			
AC Range	90~135VAC/190~245VAC			
Voltage Range	10.0~16.0VDC	20.0~31.0VDC	10.0~16.0VDC	20.0~31.0VDC
Charge Current	25A	15A	25A	15A
Fault Indication	LED Red			
Remote Control	CR10-11			
Safety	UL458		LVD (EN60950)	
EMC	FCC Part15 ClassA		CE (EN55022:2006+A1:2007)	
Operating Temp	-20~50℃			
Working Humidity	20~90%RH			
Storage Temp	-30~70℃			
Cooling	Automatically controlled cooling fan			
Weight (kg)	11			
Size (mm)	425*255*185(L*W*H)			
Application	Vehicle,Yacht,Solar power systems,Portable equipments,Power tools,Home and Office appliances			

*Note: The Specifications are subject to changes without notice.