

Portable Power station SP 1000 / SP2000



SP1000



SP2000



Large - capacity charging station



1.5 - hour fast charging



Simple and easy to use



Supports PV input for charging at any time



High - power AC output



More than ten protection functions for higher safety

SP1000 / SP2000 Product Introduction

SP 1000					
Output Specification					
AC Outlet×2	110V 60Hz or 220V 50Hz, 1000W				
Peak Power	2000W	USB - A×3	QC3.0, 5 - 12V, Max. 18W	Car Outlet×1	11 - 14V / Max. 10A
DC Outlet×2	12V 5A	Type - C×1	PD3.0, 5 - 20V, Max. 100W	Wireless Charging	15W
Input Specification					
DC Input×2	12V 10A	Battery Capacity	1058Wh	Radio	87.5 - 108MHz
Type - C Port×1	5 - 20V; Max. 100W	Battery Type	LiFePO4	Spotlight	2W
Charging Time	9h	Cycle Life	MAX 3000 cycles to 80% capacity		
General					
Weight	14KG	Package Weight	16.2KG		
Dimension	330x260x230mm	Package Dimension	440x320x290mm		

SP 2000					
Output Specification			Input Specification		
AC Outletx3	110V 60Hz or 220V 50Hz, 2400W		AC Inputx1	1500W, full charge time≈1.5h	
Peak Power	4000W			800W, full charge time≈2.5h	
DC Outletx2	12V/ Max. 8A		DC Inputx1	12V/ 24V, MAX. 8A	
USB - Ax3	QC3.0, 3.7 - 20V, Max. 24W		Solar Input	15 - 100V,	
Type - Cx3	PD3.0, 5 - 20V, Max. 65W			Max. 400W (Interface Type: XT60EW - M)	
Car Outletx1	12.6V±1V, Max. 8A		Type - C Portx3	5 - 20V; Max. 100W	
Battery		General			
Battery Capacity	2016Wh	Weight	29.5KG	Package Weight	31KG
Battery Type	LiFePO4	Dimension	420x331x270mm	Package Dimension	550x440x330mm
Cycle Life	>2000 cycles to 80% capacity				

